



## Renault - Castrol GTX RN-SPEC 0W-20 RN 17 FE

### Description

Renault - Castrol GTX RN-SPEC 0W-20 RN 17 FE is a fully synthetic oil suitable for certain diesel and gasoline engines where RN 17 FE is required

It meets high quality standards, facilitating optimum engine performance and extended component life by virtue of fast and effective lubrication across a wide temperature range.

It's more than just oil. It's liquid engineering that protects against the problems your engine faces every day.

### Application

Renault - Castrol GTX RN-SPEC 0W-20 RN 17 FE is a fully synthetic oil is designed for certain latest gasoline and diesel engines where low temperature properties and low viscosity are a requirement.

Renault - Castrol GTX RN-SPEC 0W-20 RN 17 FE is suitable for use in vehicles that require a Renault RN 17FE specification 0W-20 lubricant.

### Advantages

- Advanced engine protection under all driving conditions
- Excellent engine cleanliness
- Advanced protection against viscosity and thermal breakdown
- Premium quality base oils and anti wear additives to help extend the life of your engine
- Fast lubrication at start-up and during warm-up periods
- Advanced fuel economy
- Suitable for gasoline particulate filters (GPF) and diesel particulate filters (DPF)

## Typical Characteristics

Name	Method	Units	Renault - Castrol GTX RN-SPEC 0W-20 RN 17 FE
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	8.1
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	4386
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	38
Viscosity Index	ASTM D2270	None	195
Pour Point	ASTM D5950	°C	-45
Flash Point, PMCC	ASTM D93	°C	210
Ash, Sulphated	ASTM D874	% w t	0.78

## Product Performance Claims

Renault RN 17FE

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Renault - Castrol GTX RN-SPEC 0W-20 RN 17 FE

06 Jan 2025

Castrol, GTX and related marks are trade marks of Castrol Ltd., used under licence.

Renault is a trade mark of Renault, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

[www.castrol.com/uk](http://www.castrol.com/uk)

Page: 2/2