



Product Data

POWER1 2T

THE OIL THAT OFFERS OUTSTANDING PERFORMANCE AND PROTECTION.

Description

New Castrol POWER1 is engineered to deliver outstanding performance and protection.

Application

- Castrol POWER1 2T exceeds JASO FD and ISO-L-EGD.
- It is recommended for all 2-stroke models of motorcycles and scooters.

Advantages

Castrol POWER1 2T helps:

- Keep key engine components clean and free from carbon deposits.
- Protect from seizure under most arduous riding conditions.
- Allow fast and easy cold start.
- Ensure low levels of exhaust smoke.

Typical Characteristics

Name	Method	Units	Castrol POWER1 2T
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	36.14
Density @ 15C, Relative	ASTM D4052	g/ml	0.862
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	6.9
Appearance	Visual		Clear & Bright
Flash Point, PMCC	ASTM D93	°C	73

Performance

API TC
ISO-L-EGD
JASO FD

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

POWER1 2T
01 Dec 2023
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.castrol.com/uk